

# TM GEAR GREASE



GREASE



## Railroad traction motor gear grease

### APPLICATIONS

#### Railway traction motor

- **TM GEAR GREASE** is an NLGI 1 grade, railroad grease designed for traction motor gears. It is compounded from petroleum resins, selected base oils and a sodium soap thickener.
- It is also an excellent lubricant for various open and closed gear cases and certain slow moving open gears. It is available in drums and one pound polyethylene bags for ease of application.

### SPECIFICATIONS

ISO 6743-9: L-XCEHB 2  
DIN 51502: KP2P-30

### ADVANTAGES

#### Excellent dispensability with excellent EP properties

- Good adhesion and is easily dispersed in centralized lube systems
- Available in 1 pound plastic bags
- Excellent EP and frictional properties due to high solids content and additives
- Oxidation and corrosion resistant

#### TYPICAL CHARACTERISTICS TM GEAR GREASE #1

NLGI Grade	1
Appearance and texture	Black adhesive grease
Thickener type	sodium
Worked Penetration (ASTM D-217)	320-350
Dropping Point, °F (°C) (ASTM D 2265)	340 (171)
4-ball EP (ASTM D-2596) seizure load, kg	160
Brookfield viscosity, #3 Spindle, 4 rpm, 200 F, cps	5,000-10,000
Base Oil Viscosity, SUS @ 210 °F	1500 min

TOTAL Lubricants USA, Inc.

400 Chisholm Place, Suite 418,  
Plano, Texas 75075  
800-442-5823 or 469-241-0950  
[www.total-us.com](http://www.total-us.com)

**TM Gear Grease #1**  
Sheet updated: 5/10/2010

5 North Stiles Street  
Linden, NJ 07036  
908.862.9300 or 800.526.4127  
[www.total-us.com](http://www.total-us.com)