

# TRANSMISSION TM 80W-90



## GEAR OIL

### USES

- Gear boxes, axles, transfer boxes.
- Specially recommended for highly loaded hypoid gears.
- All types of gears when the MIL-L-2105D specification or API GL-5 is required.

### PROPERTIES

- High viscosity index.
- High Extreme-Pressure properties.
- Excellent antifoam, anticorrosive and antirust properties.
- Excellent stability in operation.

### CHARACTERISTIC

TRANSMISSION TM	Units	Grade SAE 80W-90
Volumetric mass at 15°C	kg/m <sup>3</sup>	897
Viscosity at 40°C	mm <sup>2</sup> /s	140
Viscosity at 100°C	mm <sup>2</sup> /s	14.5
Viscosity index	-	105
Flash point Cleveland	°C	208
Pour point	°C	-27

*The typical characteristics mentioned represent mean values.*

### SPECIFICATIONS

API GL-5  
MIL-L-2105D

TOTAL LUBRIFIANTS  
16, rue de la République  
92800 PUTEAUX

TRANSMISSION TM 80W-90  
January 2004



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.