



METALWORKING



## Chlorine-free Cutting Oil for General Machining.

## APPLICATIONS

VALONA 80 S is a clear, essentially odorless, yellow-amber oil of very light viscosity which is efficient over a wide working range of both metals and machining operations.
VALONA 80 S is used for light duty metalworking operations and general purpose lubricating applications. It is preferred for machining brass and copper alloys.

## **ADVANTAGES**

- Chlorine free.
- Rust and oxidation inhibited.
- Increases tool life, prevents ridging, promotes excellent surface finish.
- Excellent metal wetting ability.

TYPICAL CHARACTERISTICS	VALONA 80 S
Appearance	Clear Yellow Liquid
Color, ASTM D-1500	1.0
Viscosity at 40°C, cSt	13.6 - 15.0
Density @ 60 °F, lbs./gal.	7.16
Specific Gravity @ 60/60 °F	0.860
Flash Point, COC, °F	340
Fire Point, COC, °F	375
Copper Strip Corrosion	1A-1B
Total Sulfur Content, %wt.	< 0.40
Active Sulfur, %wt.	Nil
Chlorine Content, %wt.	Nil

## TOTAL Lubricants USA, Inc

Linden, NJ 07036 5 North Stiles Street 908.862.9300/800.526.4127 Rockingham, NC 28379 709 Airport Road 800.323.3198 / 800.526.4127 Knoxville, TN 37914 3315 Riverside Drive 800.323.3198 / 800.526.4127

TOTAL Lubricants USA, Inc. with a policy of continuous improvement, reserves the right to change specifications as our technology progresses. We are not responsible for the misuse and/or misapplication of our products. ©2008 All rights reserved. JAS 09/2008