

# VALONA GR 3308 S



METALWORKING



**TOTAL**

## Fortified Heavy Duty Grinding Oil

### APPLICATIONS

- **VALONA GR 3308 S** is grinding oil designed specifically for both rough and finish grinding of bearings.
- It is heavily fortified with a balanced blend of extreme pressure additives and lubricity agents.
- Contains no chlorine
- Contains anti-mist and anti-oxidation protection

### ADVANTAGES

- Very good extreme pressure performance
- Increases tool life
- Promotes good surface finish.
- Non-staining.
- Permits operator surveillance of the workpiece at all times.

TYPICAL CHARACTERISTICS	VALONA GR 3308 S
	Appearance
Color, ASTM D-1500	1.0
Odor	Mild petroleum
Viscosity at 40°C, cSt	8.5
Viscosity at 100°C, cSt	2.47
Density @ 60 °F, lbs./gal.	6.97
Specific Gravity @ 60/60 °F	0.841
Flash Point, COC, °F/ °C	326/ 164
Copper Strip Corrosion	1A-1B
Sulfur, %wt.	<1
Chlorine, %wt.	Nil
Lubricity Content, %	3.0
Phosphorus, ppm	<1

Revised 2/09 WHC

TOTAL Lubricants USA, Inc.

Linden, NJ 07036  
5 North Stiles Street  
908.862.9300/800.526.4127

Rockingham, NC 28379  
709 Airport Road  
800.323.3198 / 800.526.4127

Knoxville, TN 37914  
3315 Riverside Drive  
800.323.3198 / 800.526.4127