



Product Information

A product of Ashland Consumer Markets, a business unit of Ashland Inc.

VALVOLINE MaxLife™ Motor Oil

Valvoline MaxLife™ is the first motor oil specially formulated to address the unique needs of higher mileage engines. Valvoline MaxLife™ is a blend of synthetic and premium conventional basestocks with seal conditioning agents, extra cleaning agents, additional anti-wear additives and novel friction modifiers for added protection. MaxLife provides performance benefits for high mileage, new and re-built engines.

The Valvoline MaxLife™ Motor Oil Advantage

- Conditions engine seals
- Minimizes oil consumption
- Maximizes power output
- Resists thermal breakdown
- Reduces deposit formation

Approvals/Performance Levels

API SN/SM	0W-20	5W-20	5W-30	10W-30	10W-40	20W-50
API Resource Conserving	0W-20	5W-20	5W-30	10W-30	-----	-----
ILSAC GF-5	0W-20	5W-20	5W-30	10W-30	-----	-----
GM Dexos 1	-----	5W-20	5W-30	-----	-----	-----
Ford WSS-M2C945-A	-----	5W-20	-----	-----	-----	-----
Ford WSS-M2C946-A	-----	-----	5W-30	-----	-----	-----
Chrysler MS-6395	-----	5W-20	5W-30	10W-30	-----	-----
GM 6094M*	-----	5W-20	5W-30	10W-30	-----	-----
Fiat 9.55535 G2	-----	-----	-----	-----	10W-40	-----
API CF*	-----	-----	-----	10W-30	10W-40	20W-50

See operator's manual for recommended viscosity grade and API service classification.

Test	SAE 0W-20	SAE 5W-20	SAE 5W-30	SAE 10W-30	SAE 10W-40	SAE 20W-50
Vis @ 100°C (cSt)	8.6	8.8	10.7	10.7	14.9	18.9
Vis @ 40°C (cSt)	45.5	51.3	63.1	70.6	103.2	169.8
Viscosity Index	169	151	160	140	151	126
Spec Gravity @ 60°F	0.83	0.86	0.86	0.87	0.87	0.88
Density (lbs/gal)	6.9	7.2	7.2	7.2	7.2	7.3
Total Base Number	8.8	8.8	8.8	8.8	8.8	8.8
Flash Point COC (°C)	219	217	221	216	220	236
Pour Point (°C)	-51	-45	-45	-39	-42	-30
CCS cP (°C)	5900@-35C	5900@-30C	5900@-30C	5900@-25C	6200@-25C	7700@-15C
MRV TP-1 cP (°C)	29,000@-40C	22,000@-35C	23,000@-35C	20,000@-30C	26,000@-30C	23,000@-20C
Noack % off @ 250°C	13.6	12.6	10.8	10.5	10.9	6.2
Sulfated Ash	1.0	1.0	1.0	1.0	1.0	1.0
Zinc/Phosphorus, wt%	0.083/0.077	0.083/0.077	0.083/0.077	0.083/0.077	0.083/0.077	0.083/0.077
Calcium, wt. %	0.210	0.210	0.210	0.210	0.210	0.210
Sodium, wt%	0.048	0.048	0.048	0.048	0.048	0.048

*Obsolete category.

This information only applies to products manufactured in the following location(s): USA, Canada

Effective Date:	Replaces:	Author's Initials:	Pages:	Revision:
2014.11.07	2014.05.15	AS	1	007

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.

ASHLAND