

Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.



VALVOLINE MULTI-PURPOSE 2-CYCLE ENGINE OIL

Valvoline Multi-Purpose 2-Cycle engine oil is a state of the art ashless two-cycle lubricant. Premium base stocks are blended with a modern ashless detergent additive package to provide maximum performance for air- and water-cooled 2 cycle engines. This ashless system provides better protection from ring and cylinder wear under the higher operating temperatures typical of air-cooled service. It is pre-diluted for ease of mixing with gasoline and may also be used in direct injector systems.

Valvoline Multi-Purpose 2-Cycle Lubricant provides excellent protection against rust, wear, corrosion, piston scuffing and ring sticking.

It is recommended for 2-cycle engines in lawn mowers, motor scooters, snowmobiles, chain saws, portable generators, snow blowers and outboards. This oil may be used where manufacturers recommend fuel/oil ratios from 11:1 to 100:1. It meets NMMA TC-W3 warranty and service requirements.

Approvals

Japanese JASO-FB category
NMMA (formerly BIA) TC-W3 certified

Typical Properties

Gravity (API)	31.9
Vis @ 100°C (cSt)	6.70
Vis @ -25°C, cP	3000
Pour Point, °C max	-36
Sulfated Ash, wt%	Nil
Color	Blue-Green
Flash Point (D-93), °C	65

This information only applies to products manufactured in the following location(s): USA, Canada.

Effective Date:	Replaces:	Author's Initials:	Code
01-19-15	05-20-13	AS	