

Product Information



A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC.

VALVOLINE™ UNITRAC™ FLUID

Valvoline™ Unitrac™ Fluid is a high performance, multi-purpose all-weather fluid designed for agricultural tractors and off-highway equipment. Valvoline™ Unitrac™ Fluid is uniquely formulated to provide excellent antiwear, oxidation, ferrous rust, copper corrosion, sludge and varnish protection. It is designed to reduce wet brake and PTO chatter. This product is recommended for use in the hydraulic systems, final drives, transmissions, differentials, wet brake systems, PTOs and hydrostatic drives.

Meets or exceeds the following specifications(Where appropriate viscosity grade applies):

John Deere JDM J20C,

New Holland Group(Ford New Holland) – FNHA-2-C-201.00(134D), FNHA-2-C-200.00(Hydraulic Oil 134)

Massey Ferguson M1129A, M1135, M1139, M1141(Permatran®III), M1143, M1145,

Case Corporation(Case I.H., J.I. Case) – MS-1207(Hy-Tran® Plus), MS-1210/JIC-143,144,145(TCH Fluid), MS-1209(Hy-Tran Ultra)

Kubota UDT Hydraulic Fluid, Universal Transdraulic Fluid

White Farm(Oliver) – Q-1826 Hydraulic, Transmission Fluid HTF)

Case New Holland MAT 3505, MAT 3525, MAT 3526, ESN M2C86B, ESN M2C86C

Agco(Duetz-Allis) – Power Fluid 821XL, 272843

Steiger Hydraulic/Transmission Fluid SEMS 17001

Landini Tractor II Hydraulic Fluid; Hesston Fiat Oilofiat Tutela Multi-F

Sundstrand Hydrostatic Transmission Fluid, Hydraulic Fluids

Allison Type C-4 Fluid

Komatsu AXO 80

Denison Hydraulic Fluid HF-0, HF-2, HF-1 All Pumps, Vickers M-2950-S Mobil Hydraulic & I-286-S Industrial Hydraulics

Clark Lift Truck Transmission Fluid TA12, TA18, HR500, HR600

Volvo VCE 1273.03, WB 101

Meets or exceeds the following older specifications(Where appropriate viscosity grade applies):

John Deere JDM J20A, J20B, J14B, & JD 303; Ford New Holland ESN-M2C134-C, ESN-M2C134B, ESN-M2C134A, ESN-M2C86B, ESN-M2C53A, ESN-M2C48-B&C; Massey Ferguson M-1129-A, M-1127-B, M-1127-A, M-1110; Case B-6(HY-TRAN®), MS-1206(PTF), MS-1210, MS-1205, MS-1204/JIC-185, JIC-144, JIC-143, B-5; White Farm(Oliver) Q-1802(Type 55 Fluid), Q-1766B(Universal HTF), Q-1722(White MP Tractor Oil), Q-1705(Universal HTF); Agco(Allis) 257541, 246634; Versatile Hydraulic /Gear Fluid Spec 24M, Spec 23M; Hesston Fiat AF-87; Oliver Q-1802(Type 55), Allison C-3 Fluid; Caterpillar TO-2; Allis Chalmers PF 821XL; API GL-4;

Test	Typical Property
Specific Gravity @ 15.5°F	0.871
CCS @ -25°C, cP, max	7000
Brookfield Vis @ -35°C, cP	32,000
Vis @ 100°C (cSt)	9.4
Vis @ 40°C (cSt)	58
Viscosity Index	141
Pour Point °C	-45
Zn wt%	0.13

Part Numbers

Bulk	VV8100
55 Gallon Drum	VV810
5 Gallon Pail	VV813
Tote	853217

This information only applies to products manufactured in the following location(s): USA

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages	Code
07/31/14		01/16/13	KD	1	Rev. 005

ASHLAND